

C: Five Lanes - Curb & Gutter

Typical for major thoroughfares, cross section "C" is desirable where frequent left turns are anticipated as a result of abutting development or frequent street intersections.

D: Six Lanes Divided with Raised Median - Curb & Gutter**E: Four Lanes Divided with Raised Median - Curb and Gutter**

Cross sections "D" and "E" are typically used on major thoroughfares where left turns and intersection streets are not as frequent. Left turns would be restricted to a few selected intersections. The 16-ft median is the minimum recommended for an urban boulevard-type cross section. In most instances, monolithic construction should be utilized due to greater cost effectiveness, ease and speed of placement, and reduced future maintenance requirements. In certain cases, grass or landscaped medians result in greatly increased maintenance costs and an increase danger to maintenance personnel. Non-monolithic medians should only be recommended when the above concerns are addressed.

F: Four Lanes Divided - Boulevard, Grass Median

Cross section "F" is typically recommended for urban boulevards or parkways to enhance the urban environment and to improve the compatibility of major thoroughfares with residential areas. A minimum median width of 24 ft is recommended, with 30 ft being desirable.

G: Four Lanes - Curb and Gutter

Cross section "G" is recommended for major thoroughfares where projected travel indicates a need for four travel lanes but traffic is not excessively high, left turning movements are light, and right-of-way is restricted. An additional left turn lane would likely be required at major intersections. This cross section should be used only if the above criteria are met. If right-of-way is not restricted, future strip development could take place and the inner lanes could become de facto left turn lanes.

H: Three Lanes - Curb and Gutter

In urban environments, thoroughfares that are proposed to function as one-way traffic carriers would typically require cross section "H".

I: Two Lanes – Curb and Gutter, Parking both sides**J: Two Lanes – Curb and Gutter, Parking one side**

Cross section "I" and "J" are usually recommended for urban minor thoroughfares since these facilities usually serve both land service and traffic service functions. Cross-section "I" would be used on those minor thoroughfares where parking on both sides is needed as a result of more intense development.